



標準 Standard	規格 Size	單重 KG/PC	外径 D	內徑 B	厚度 T	槽內徑 B1	槽深 t	中心距 K	孔數 J	孔徑 H	R
JWWA JM	3" — 80A	3.53	211	97	18	119	7	168	4	19	3
JWWA JM	4" — 100A	4.12	238	125	18	149	7	195	4	19	3
JWWA JM	5" — 125A	4.95	263	155	20	179	7	220	6	19	3
JWWA JM	6" — 150A	6.05	290	180	22	208	10	247	6	19	3
JWWA JM	8" — 200A	7.52	342	231	22	255	10	299	8	19	3
JWWA JM	10" — 250A	11.47	410	282	24	310	10	360	8	23	3
JWWA JM	12" — 300A	13.53	464	333	24	360	10	414	10	23	3
JWWA JM	14" — 350A	18.42	530	390	26	415	10	472	10	25	5
JWWA JM	16" — 400A	20.48	582	437	26	473	10	524	12	25	5
JWWA JM	18" — 450A	27.84	652	492	28	528	10	585	12	27	5
JWWA JM	20" — 500A	31.02	706	540	28	586	10	639	12	27	5
JWWA JM	24" — 600A	38.55	810	640	30	690	12	743	16	27	5
JWWA JM	28" — 700A	50.62	928	744	32	791	15	854	16	33	5
JWWA JM	32" — 800A	61.55	1034	845	34	897	15	960	20	33	5
JWWA JM	36" — 900A	80.65	1156	950	36	1010	15	1073	20	33	5
JWWA JM	40" — 1000A	93.16	1262	1050	38	1115	18	1179	24	33	5
JWWA JM	44" — 1100A	111.86	1366	1160	41	1210	18	1283	24	33	5
JWWA JM	48" — 1200A	123.87	1470	1260	43	1330	18	1387	28	33	5
JWWA JM	60" — 1500A	183.35	1800	1570	48	1650	20	1710	32	39	5
JWWA JM	66" — 1650A	229.11	1965	1730	53	1810	20	1870	40	39	5
JWWA JM	80" — 2000A	287.07	2325	2080	58	2160	30	2230	48	46	5
JWWA JM	88" — 2200A	373.33	2550	2280	60	2360	30	2440	52	46	5

※ 法蘭各部尺寸公差

外 徑 (D) +1.0MM-0MM

內 徑 (d) +0.5MM-0MM

厚 度 (T) +1.0MM-0MM

中 心 距 (C) ±0.5MM



蚨鑫国际有限公司

FU XIN INTERNATIONAL CO., LIMITED

JWWA JM

畫 圖

製 表

審 核

Tyler shao

標 準

材 質

日 期

Rubber joint Flange

Carbon Steel: Q235B

04/Sep/2021